## Cylinder 5 stage front end with plain eye

# Ø51 -.012 R45 Ø205 1515 <sup>40</sup> MOUNTING CENTRES\* 1.25" BSP **INLET PORT** Ø60 -.10 8 Customer to fit 2 x 1/8" BSP nipples for greasing. R135 NG5 or NG6 260 217 395

### \*Includes 9mm Pull Out Last Stage Chrome Plated



#### Edbro plc

Nelson Street, Bolton, Lancashire BL3 2JJ UK Tel +44 (0) 1204 528888 Fax +44 (0) 1204 531957 Email: postmaster@edbro.com Web: www.edbro.com

### CS170E56233B70A02

SPECIFICATION	RATED CAPACITY: 30-40 TONNES***						
Stage	Diameter	Length	Stroke	Swept Volume			
-	-	-	-	-			
0	199	1475	-	-			
1	176	1440	1217	30			
2	155	1440	1237	23			
3	136	1440	1247	18			
4	117	1440	1262	14			
5	98	1465	1267	10			
Final stroke reduced by	0	Total (+5/-10)	6230	95			
Cylinder Mass (Kg)	222.36	Priming Volume		19			
Rated Pressure (Bar)	135	Total Volum	114				
Maximum Pressure (Bar)	175	Max. first sta	260 KN				

### \*\*\*TIPPING CAPACITY AT RATED PRESSURE

	E	BODY LENGTH (BL)							
	77	50	8250		8750		ОН		
	31	49°	30	46°			150		
	35	52°	32	48°	30	45°	450		
	(40)	(54°)	36	50°	33	47°	750		
Tipping angle $(\theta)$									

Body + payload mass,W (tonne)

### For guidance only;

Higher Rated Pressures may be possible. To check your application, email Edbro plc at <applications@edbro.co.uk>

#### NOTES

- If hydraulic pressure is used to limit overloading, the system relief valve must be set to the Rated Pressure unless agreed otherwise by Edbro
- The system relief valve can be set to Maximum Pressure if the load is limited by other means. See RATINGS page for advice
- This cylinder is for lifting purposes only and sideload conditions must be avoided
- Cylinder is painted in primer paint to RAL5013
- See bracket options page BRKT01, BRKT02
- See installation instructions INSTALL01
- Use oil according to specification OIL01

Technical Specifications are subject to change without notice Date Created/Updated: 26 August 2009 07:47:15 Refer www.edbro.com to confirm latest specification All dimensions are in 'mm', unless otherwise stated