## Cylinder 5 stage front end with Outer Cover


# \*\*ALLOW 50mm TO REMOVE **CAP FOR SERVICING Edbro** Edbro 462 330 345 0 MOUNTING CENTRES Ø60 -.10 2X 1.25" BSP INLET PORT Ø60 -.10 Customer to fit 2 x 1/8" BSP nipples R140 for greasing. NG5 or NG6 260 230 392

### C\$180057233T19A11

SPECIFICATION	R	60 TONNES***			
Stage	Diameter	Length	Stroke	Swept Volume	
OUTER COVER	261	1345	-	-	
0	211	1675	-	-	
1	188	1640	1414	39	
2	167	1640	1437	31	
3	147	1640	1447	25	
4	127	1640	1462	19	
5	105	1640	1467	13	
Final stroke reduced by	0	Total (+5/-10)	7227	127	
Cylinder Mass (Kg)	372.09	Priming Volume  Total Volume (Litres)		23	
Rated Pressure (Bar)	175			150	
Maximum Pressure (Bar)	175	Max. first sta	260 KN		

#### \*\*\*TIPPING CAPACITY AT RATED PRESSURE

d = 229 ; r = 900



	BODY LENGTH (BL)						ОН			
	85	8500		9000		9500				
	49	50°	46	47°	44	45°	150			
	54	52°	50	49°	47	46°	450			
	(60)	(54°)	55	51°	51	48°	750			
Tipping angle $(\theta)$										

Body + payload mass,W (tonne)

#### For guidance only;

Higher Rated Pressures may be possible. To check your application, email Edbro plc at <applications@edbro.co.uk>

#### NOTES

- If hydraulic pressure is used to limit overloading, the system relief valve must be set to the Rated Pressure unless agreed otherwise by Edbro
- The system relief valve can be set to Maximum Pressure if the load is limited by other means. See RATINGS page for advice
- This cylinder is for lifting purposes only and sideload conditions must be avoided
- Cylinder is painted in primer paint to RAL5013
- See bracket options page BRKT01, BRKT02
- See installation instructions INSTALL01
- Use oil according to specification OIL01

\*Includes 12mm Pull Out



Edbro plc

Nelson Street, Bolton, Lancashire BL3 2JJ UK
Tel +44 (0) 1204 528888 Fax +44 (0) 1204 531957
Email: postmaster@edbro.com Web: www.edbro.com

Technical Specifications are subject to change without notice Date Created/Updated: 26 August 2009 14:55:23 Refer www.edbro.com to confirm latest specification All dimensions are in 'mm', unless otherwise stated