Cylinder 5 stage front end with Outer Cover


ALLOW 50mm TO REMOVE **CAP FOR SERVICING Edbro Edbro 462 330 2176** Ø60 -.10 30°MAX 550 0 MOUNTING CENTRES -1.25" BSP INLET PORT 190 Ø60 -.10 Customer to fit 2 x 1/8" BSP nipples for greasing. R140 NG5 or NG6 260 392

CS180059483B19A12

SPECIFICATION	R	ATED CAPA	CITY: 29-3	34 TONNES***
Stage	Diameter	Length	Stroke	Swept Volume
OUTER COVER	261	1590	-	-
0	211	2125	-	-
1	188	2090	1864	52
2	167	2090	1887	41
3	147	2090	1897	32
4	127	2090	1912	24
5	105	2090	1917	17
Final stroke reduced by	0	Total (+5/-10)	9477	166
Cylinder Mass (Kg)	447.13	Priming \	31	
Rated Pressure (Bar)	120	Total Volum	197	
Maximum Pressure (Bar)	175	Max. first sta	260 KN	

***TIPPING CAPACITY AT RATED PRESSURE

d = 229 : r = 900



BODY LENGTH (BL)							
115	500	12000		12500		ОН	
30	49°	29	46°			150	
32	50°	31	48°	30	46°	450	
(34)	(51°)	33	49°	31	47°	750	
Tipping angle (θ)							

Body + payload mass,W (tonne)

For guidance only:

Higher Rated Pressures may be possible. To check your application, email Edbro plc at <applications@edbro.co.uk>

NOTES

- If hydraulic pressure is used to limit overloading, the system relief valve must be set to the Rated Pressure unless agreed otherwise by Edbro
- The system relief valve can be set to Maximum Pressure if the load is limited by other means. See RATINGS page for advice
- This cylinder is for lifting purposes only and sideload conditions must be avoided
- Cylinder is painted in primer paint to RAL5013
- See bracket options page BRKT01, BRKT02
- See installation instructions INSTALL01
- Use oil according to specification OIL01

*Includes 12mm Pull Out



Edbro plc

Nelson Street, Bolton, Lancashire BL3 2JJ UK Tel +44 (0) 1204 528888 Fax +44 (0) 1204 531957 Email: postmaster@edbro.com Web: www.edbro.com

Technical Specifications are subject to change without notice Date Created/Updated: 26 August 2009 14:47:05 Refer www.edbro.com to confirm latest specification All dimensions are in 'mm', unless otherwise stated