


# Cylinder 5 stage front end with plain eye


CS18LE57233B19A03



**SPECIFICATION** **TIPPING CAPACITY : 31-40 TONNES\*\*\***

Stage	Diameter	Length	Stroke	Swept Volume
-	-	-	-	-
0	211	1675	-	-
1	188	1640	1420	39
2	167	1640	1437	31
3	147	1640	1447	25
4	127	1640	1462	19
5	105	1665	1467	13
			Total (+5/-10)	127
Final stroke reduced by	0	Priming Volume		23.5
Cylinder Mass (Kg)	278	Total Volume (Litres)		150.5
Maximum Pressure (Bar)	190	Max. first stage thrust		200 KN

**\*\*\*TIPPING CAPACITY AT WORKING PRESSURE**




BODY LENGTH (BL)						OH
9250		9750		10250		
34	48°	32	45°	31	43°	150
37	49°	35	47°	33	44°	450
40	51°	37	48°	35	45°	750

$d = 0$ ;  $r = 900$ ; Working Pressure 135 bar  
**For guidance only;**  
 Higher working pressures and tipping capacities may be possible.  
 To check your application email - [applications@edbro.co.uk](mailto:applications@edbro.co.uk)

**NOTES**

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer paint to RAL5013
3. Refer to [www.edbro.com](http://www.edbro.com) for:-
  - Bracket details
  - Installation instructions that must be observed
  - Correct oil selection
  - An explanation of tipping capacity

\*Includes 7mm Pull Out. Last Stage Chrome Plated



CS18LE57233B19A03