


Cylinder 3 stage front end with outer cover

****ALLOW 50mm TO REMOVE CAP FOR SERVICING**




***Includes 10mm Pull Out.**

CX1000303359A101

SPECIFICATION		TIPPING CAPACITY : 13-14 TONNES***		
Stage	Diameter	Length	Stroke	Swept Volume
OUTER COVER	152	1070	-	-
0	117	1270	-	-
1	98	1290	1110	8
2	79	1290	1122	6
4	63	1290	1127	4
Total (+5/-10)			3359	18
Final stroke reduced by	0	Priming Volume		3
Cylinder Mass (Kg)	125	Total Volume (Litres)		21
Maximum Pressure (Bar)	175	Oil Tank Capacity (L)		25

***TIPPING CAPACITY AT WORKING PRESSURE



BODY LENGTH (BL)						OH
4000		4250		4500		
14	50°	13	47°	13	44°	150
14	55°	14	51°	14	48°	450
				14	52°	750

$d = 0$; $r = 900$; Working Pressure 150 bar

For guidance only;

Higher working pressures and tipping capacities may be possible.
To check your application email - applications@edbro.co.uk

NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer paint to RAL5013
3. Refer to www.edbro.com for:-
 - Bracket details
 - Installation instructions that must be observed
 - Correct oil selection
 - An explanation of tipping capacity



JOST UK Ltd
Edbro House, Nelson Street, Bolton, England, BL3 2JJ
Tel +44 (0) 1204 528888 Fax +44 (0) 1204 531957
Email: sales-uk@jost-world.com Web: www.edbro.com

Technical Specifications are subject to change without notice
Date Created/Updated: 07 October 2020
Refer www.edbro.com to confirm latest specification
All dimensions are in 'mm', unless otherwise stated