



Features

- Top mounted valve plate for easy maintenance
- Compatible with Edbro valve CT200
- Integral oil level sight glass
- Tanks finished in RAL7021 grey superior primer
- Integral stainless steel return filter 60 micron included
- 1.5" BSP suction ports
- Auxiliary 1" BSP return port with plug fitted
- Pressure tested
- Internally cleaned

Part Number	Dimensions(mm)							Total capacity (litres)	Useable capacity (litres)	Material	Mass (kg)
	H*	B	L	X	S	M	K				
<i>TANKS AVAILABLE EX-STOCK</i>											
OT7310F/135/03	700	280	970	200	60	100	39	165	135	Steel	44
OT7311F/155/03	700	280	1100	200	60	100	39	185	155	Steel	50
OT7314F/193/03	700	280	1390	200	60	100	39	235	193	Steel	58

Additional required parts: (not supplied with oil tank)
 AF97 oil filler breather (*add 65mm to H dimension for filler cap).
 1 x TMK3 tank washer kit required.

*Add to dimension H 20mm for valve plate, plus 80mm for valve and bolts

Tank Selection:

Select a tank that has a useable capacity greater than the swept volume of the cylinder / working volume of the application.

Tank Capacity:

Total capacity is the amount of oil to fill the tank and leave 60mm air gap above the oil. Useable capacity is calculated assuming a minimum of 100mm oil depth left at the bottom of the tank.

Oil Tanks: Rear Mount Tractor Chassis

SPARE PARTS

Description	Part No.
Valve Plate for CT200 Valve	BP240
Gasket for Filter	FW190
M8 Staines Steel Cap Head Screw	KS218/M8/25/SS
Filter Assembly	PM646
Stainless Steel Strap (1730 Long)	OT7310SSTRAP
Rubber Strap (1550 Long)	OT7310RUBBERSTRAP
Rubber Base	OT7310RUBBERBASE
Tank Mount Bracket and Strap Kit	OT7310BRACKET/STRAP

