

## Tip with safety not guess work

- Continual monitoring of tipping angle during operation reduces the risk of accidents
- Tip lock out facility prevents tipping on side inclines above a user defined angle
- Optimised driver safety to reduce risk of injury

- Reduced risk of claims
- Dual voltage

# Inclinometer

#### **Features**

- Small compact in cab LED display unit
- Full multi language installation guide & operating instructions
- IP rated connectors
- Managers Key for Safety Lock on system and control angle settings
- 3° Factory Set Safety Angle





#### **Electrical**

Operating Voltage	DC 12-24 V
Operating Current	350 mA
Fuse Rating	1A

#### Sensor

Accuracy	+/- 0.1º
Range	0.0º to 9.9º
Repeatability	+/- 0.1º

### **Technical Specification**

Waterproof rating	Sensor: IP69K Display: IP52
Relative Humidity	Sensor and Display:%00
Operating Temperature	-10 to +55 ºC
Size	Display: 106 x 67 x 22 mm Sensor: 110 x 55 x 25 mm
Kit Weight	1.2 kg
Cable Length	Power Lead: 2 m
Valve Lead	5 m
Suzi	max 4 m
Tractor Cable (RINC02)	7 m
Trailer Cable (TINC02)	13 m

### **Order Part Code**

Rigid/Truck	RINC02
Trailer	TINC02

Display Unit x 1



where the state of the state of

Sensor Unit x 1

Cut Off Valve x 1



Mounting Bracket x 1



Power / Valve Cable x 1



Sensor Cable x 1 Rigid Kit Only



Trailer Cable x 1
Trailer Kit Only



Tractor Cable x 1
Trailer Kit Only



Suzi Cable x 1 Trailer Kit Only



1A Fuse & Fuse Holder x 1



Managers Key x 1



Instruction Sheet x 2



2.9 x 9.5 ST Screw x 2



M4 Washer x 2



M4 x 20 SS Bolt x 2



M4 Nyloc Nut x 2



200 mm Cable Tie x 25

200 Hilli Cable He X 23